

Triticale Official Purchasing Specification

Quality Standards

	Spec	Min/Max
Test Weight	56	50
Moisture	13%	13.5%
Plump	70%	60%
Thins	0%	5%

Foreign Material

	Spec	Min/Max
FM	0%	3%
Total Other	0%	2%
Grains		
Ergot	0%	.04%

Damage

	Spec	Min/Max
Total	0%	4%
Damage		
Vomitoxin	0 ppm	1 ppm
Heated	0%	0.2%
Falling #	170	150

Test Weight Conversions

Lb/W.bu	g/0.5 L	Lb/W.bu	g/0.5 L
49	316	54	348
49.5	319	54.5	351
50	322	55	354
50.4	325	55.5	357
50.9	328	56	361
51.5	332	56.5	364
52	335	57	367
52.5	338	57.5	370
52.9	341	58	374
53.5	345	58.5	377

Discounts may apply to any grain delivered out of spec.

- » FM –Thru 8/64" triangle sieve
- » Plump On top of 6/64" slotted sieve
- » Moisture Tested on Dickey John

Pest/Pesticide/Odor Restrictions

- Triticale must NOT contain signs of infestation (dead or alive) or insect damaged kernels
- Triticale which has been treated with glyphosate as a pre-harvest desiccant will not be accepted
- Triticale must not contain detectable levels of pesticide, chemicals, or any objectionable odors

Contacts

Brian Krause brian.krause@oegema.ca

Dan Patton dan.patton@oegema.ca

Conventional Triticale Discount Schedule (Based on W.Bu, US\$)

Foreign Material (FM)

• All FM is deducted as dockage